

Lady Design Marmorino

Product description

Type

This product is a high quality limestone paint that gives a soft stone finish.

Features and benefits

This product gives your interior the noble touch of the old polished plaster. With highly versatile application methods, you can recreate some of the most iconic designs.

Recommended use

It is recommended for hotels, restaurants, villas and all other prestigious interiors.

Substrate

Cement plaster, concrete, block work, rendered surfaces etc.
Please refer to the Decorative Sales Department for technical advice.

Product data

Packaging size	4 L and 18 L
Colours	As per Lady Design Marmorino Colour Tools.
Solids by volume	50 ± 2 volume%
pH value	12 to 13
VOC comments	2.91 g/l as per EU Directive 2004/42/EC Theoretical

Application data

Application equipment / methods

Apply the first coat of Lady Design Marmorino as a smooth coat with stainless steel trowel and let it dry for 24 hours. Then apply the second coat with the design.

To ensure the desired texture and appearance is achieved, it is required to have a team of skilled applicators or professional painters.

(Important!) Product requires mixing/ stirring prior to every use for easy trowel application. For the 18L pack size, it is recommended to use mechanical agitator before application.

Film thickness per coat

Typical recommended range

Dry film thickness : 500 microns

Wet film thickness : 1000 microns

Spreading rate per coat (m²/l)- : 1

Film thickness will vary and are calculated as an average.

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

Thinner

No thinning is required.

Drying times

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature 20 °C

Surface (touch) dry	2 h
Hard dry	24 h
Dry to over coat, minimum	24 h

Directions for use

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

Recommended paint system

Primer

Fenomastic Emulsion Primer : 1 coat

Topcoat

Lady Design Marmorino : 2 coats

Health and safety

Product can cause serious eye damage and skin corrosion/irritation upon direct contact. It is important to always wear protective gloves and eye goggles or face protection when using Lady Design Marmorino.

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.