

Penguard FC Comp B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Penguard FC Comp B
Product code : 4680
Product description : Hardener.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use
 Use in coatings - Professional use

See Annex to the Safety data sheet for additional information in the Exposure Scenario(s).

1.3 Details of the supplier of the safety data sheet

Jotun Paints Co LLC,
 P.O.Box 672-C.P.O,
 Postal Code - 111
 Sultanate of Oman
 Tel: 00968-626100
 Fax:00968-626105
 SDSJotun@jotun.com

1.4 Emergency telephone number

SHE Dept. Jotun AS, Norway
 +47 33 45 70 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
 Skin Irrit. 2, H315
 Eye Dam. 1, H318
 Skin Sens. 1, H317
 STOT SE 3, H335
 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.
 See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Penguard FC Comp B

SECTION 2: Hazards identification

Signal word	: Danger.
Hazard statements	: H226 - Flammable liquid and vapour. H318 - Causes serious eye damage. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation. H411 - Toxic to aquatic life with long lasting effects.
<u>Precautionary statements</u>	
General	: Not applicable.
Prevention	: P280 - Wear protective gloves. Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P261 - Avoid breathing vapour.
Response	: P391 - Collect spillage. P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P333 + P313 - If skin irritation or rash occurs: Get medical attention. P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: P403 - Store in a well-ventilated place. P235 - Keep cool.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine xylene 2,4,6-tris(dimethylaminomethyl)phenol amines, polyethylenepoly-, triethylenetetramine fraction
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
<u>Special packaging requirements</u>	
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Other hazards which do not result in classification	: None known.

Penguard FC Comp B**SECTION 3: Composition/information on ingredients****3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	Weight %	Regulation (EC) No. 1272/2008 [CLP]	Type
fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	CAS: 68082-29-1	≥50 - ≤75	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	<10	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304	[1] [2]
2,4,6-tris(dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	<5	Skin Corr. 1C, H314 Eye Dam. 1, H318	[1]
amines, polyethylenepoly-, triethylenetetramine fraction	REACH #: 01-2119487919-13 EC: 292-588-2 CAS: 90640-67-8	<1	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Penguard FC Comp B

SECTION 4: First aid measures

- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Ingestion may cause nausea, diarrhea and vomiting.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Penguard FC Comp B

SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.
In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.
Keep away from heat, sparks and flame. No sparking tools should be used.
Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
Put on appropriate personal protective equipment (see Section 8).
Never use pressure to empty. Container is not a pressure vessel.
Always keep in containers made from the same material as the original one.
Comply with the health and safety at work laws.
Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities

Penguard FC Comp B

SECTION 7: Handling and storage

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EU OEL (Europe, 2/2017). Absorbed through skin. Notes: list of indicative occupational exposure limit values STEL: 442 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 221 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
ethylbenzene	EU OEL (Europe, 2/2017). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 100 ppm 8 hours. TWA: 442 mg/m ³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m ³ 15 minutes.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value	Population	Effects
xylene	Short term Inhalation	289 mg/m ³	Workers	Systemic
	Short term Inhalation	289 mg/m ³	Workers	Local
	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	Long term Inhalation	77 mg/m ³	Workers	Systemic
	Long term Dermal	108 mg/kg bw/day	Consumers	Systemic

Penguard FC Comp B

SECTION 8: Exposure controls/personal protection

ethylbenzene	Long term Inhalation	14.8 mg/m ³	Consumers	Systemic
	Long term Oral	1.6 mg/kg bw/day	Consumers	Systemic
	Short term Inhalation	293 mg/m ³	Workers	Local
	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	Long term Inhalation	77 mg/m ³	Workers	Systemic
	Long term Inhalation	15 mg/m ³	Consumers	Systemic
	Long term Oral	1.6 mg/kg bw/day	Consumers	Systemic
2,4,6-tris(dimethylaminomethyl)phenol	Long term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	Long term Inhalation	0.31 mg/m ³	Workers	Systemic
amines, polyethylenepoly-, triethylenetetramine fraction	Short term Inhalation	5380 mg/m ³	Workers	Systemic
	Long term Dermal	0.57 mg/kg bw/day	Workers	Systemic
	Long term Inhalation	1 mg/m ³	Workers	Systemic
	Long term Dermal	0.028 mg/m ³	Workers	Local
	Short term Dermal	8 mg/kg bw/day	Consumers	Systemic
	Short term Inhalation	1600 mg/m ³	Consumers	Systemic
	Short term Oral	20 mg/kg bw/day	Consumers	Systemic
	Short term Dermal	1 mg/cm ²	Consumers	Local
	Short term Dermal	0.25 mg/kg bw/day	Consumers	Local
	Long term Inhalation	0.29 mg/m ³	Consumers	Systemic
	Long term Oral	0.41 mg/kg bw/day	Consumers	Systemic
	Long term Dermal	0.43 mg/cm ²	Consumers	Local

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
xylene	Fresh water	0.327 mg/l	-
	Marine	0.327 mg/l	-
	Sewage Treatment Plant	6.58 mg/l	-
	Fresh water sediment	12.46 mg/kg dwt	-
	Marine water sediment	12.46 mg/kg dwt	-
	Soil	2.31 mg/kg dwt	-
ethylbenzene	Fresh water	0.1 mg/l	-
	Marine	0.01 mg/l	-
	Sewage Treatment Plant	9.6 mg/l	-
	Fresh water sediment	13.7 mg/kg dwt	-
	Soil	2.68 mg/kg dwt	-
	Secondary Poisoning	20 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	Fresh water	0.084 mg/l	-
	Marine	0.0084 mg/l	-
	Sewage Treatment Plant	0.2 mg/l	-
	Plant		

Penguard FC Comp B

SECTION 8: Exposure controls/personal protection

amines, polyethylenepoly-, triethylenetetramine fraction	Fresh water	190 µg/l	Assessment Factors
	Fresh water sediment	95.9 mg/kg	Equilibrium Partitioning
	Marine water	38 µg/l	Assessment Factors
	Marine water sediment	19.2 mg/kg	Equilibrium Partitioning
	Soil	19.1 mg/kg	Equilibrium Partitioning
	Sewage Treatment Plant	4.25 mg/l	Assessment Factors
	Secondary Poisoning	0.18 mg/kg	Assessment Factors

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Gloves : There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. Wear suitable gloves tested to EN374. Not recommended, gloves(breakthrough time) < 1 hour: PVC Recommended, gloves(breakthrough time) > 8 hours: 4H, Teflon, polyvinyl alcohol (PVA), nitrile rubber May be used, gloves(breakthrough time) 4 - 8 hours: neoprene, butyl rubber

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Penguard FC Comp B

SECTION 8: Exposure controls/personal protection

- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387(as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Yellowish-brown.
- Odour** : Characteristic.
- Odour threshold** : Not applicable.
- pH** : Not applicable.
- Melting point/freezing point** : Not applicable.
- Initial boiling point and boiling range** : Lowest known value: 136.1°C (277°F) (ethylbenzene). Weighted average: 136.14°C (277.1°F)
- Flash point** : Closed cup: 25°C
- Evaporation rate** : Highest known value: 0.84 (ethylbenzene) Weighted average: 0.79compared with butyl acetate
- Flammability (solid, gas)** : Not applicable.
- Upper/lower flammability or explosive limits** : 0.8 - 6.7%
- Vapour pressure** : Highest known value: 1.2 kPa (9.3 mm Hg) (at 20°C) (ethylbenzene). Weighted average: 0.28 kPa (2.1 mm Hg) (at 20°C)
- Vapour density** : Highest known value: 3.7 (Air = 1) (xylene). Weighted average: 3.7 (Air = 1)
- Density** : 0.942 g/cm³
- Solubility(ies)** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/ water** : Not available.
- Auto-ignition temperature** : Lowest known value: 382°C (719.6°F) (2,4,6-tris(dimethylaminomethyl)phenol).
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C): >0.205 cm²/s (>20.5 mm²/s)
- Explosive properties** : Not available.
- Oxidising properties** : Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Penguard FC Comp B**SECTION 10: Stability and reactivity**

10.6 Hazardous decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Ingestion may cause nausea, diarrhea and vomiting.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LC50 Inhalation Vapour	Rat	20 mg/l	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
	TDL ₀ Dermal	Rabbit	4300 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat - Male	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Oral	Rat	1673 mg/kg	-
	LD50 Dermal	Rabbit - Male, Female	1465.4 mg/kg	-
amines, polyethylenepoly-, triethylenetetramine fraction	LD50 Oral	Rat - Male, Female	1716.2 mg/kg	-

Acute toxicity estimates

Route	ATE value
Dermal	5135.4 mg/kg
Inhalation (vapours)	67.93 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Eyes - Irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Mammal - species unspecified	-	-	-
xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
2,4,6-tris (dimethylaminomethyl) phenol	Eyes - Severe irritant	Rabbit	-	24 hours 50 µg	-
	Skin - Severe irritant	Rat	-	0.25 ml	-

Sensitisation

Penguard FC Comp B**SECTION 11: Toxicological information**

Product/ingredient name	Route of exposure	Species	Result
fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine amines, polyethylenepoly-, triethylenetetramine fraction	skin	Mammal - species unspecified	Sensitising
	skin	Mammal - species unspecified	Sensitising

Mutagenicity

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	Not determined	hearing organs

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Other information : None identified.

SECTION 12: Ecological information**12.1 Toxicity**

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
ethylbenzene	Acute EC50 7.2 mg/l	Algae	48 hours
	Acute EC50 2.93 mg/l	Daphnia	48 hours
	Acute LC50 4.2 mg/l	Fish	96 hours
	Acute EC50 20 mg/l	Algae	72 hours
	Acute EC50 31.1 mg/l	Daphnia	48 hours
amines, polyethylenepoly-, triethylenetetramine fraction	Acute LC50 330 mg/l	Fish	96 hours

This material is toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Not available.

Penguard FC Comp B**SECTION 12: Ecological information**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
ethylbenzene	-	-	Readily
amines, polyethylenepoly-, triethylenetetramine fraction	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	8.1 to 25.9	low
ethylbenzene	3.6	-	low
2,4,6-tris (dimethylaminomethyl) phenol	0.219	-	low
amines, polyethylenepoly-, triethylenetetramine fraction	-2.65	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC) : 08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Penguard FC Comp B





SECTION 13: Disposal considerations

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging CEPE Paint Guidelines	15 01 10*	European waste catalogue (EWC) packaging containing residues of or contaminated by hazardous substances
---	-----------	---

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	Paint related material	Paint related material	Paint related material. Marine pollutant (fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine)	Paint related material
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Hazard identification number 30
Tunnel code (D/E)
- ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Emergency schedules F-E, S-E
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Penguard FC Comp B

SECTION 14: Transport information

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not applicable.

Europe inventory : Not determined.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Penguard FC Comp B

SECTION 15: Regulatory information

15.2 Chemical safety assessment : Not applicable.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4
Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4
Aquatic Chronic 2, H411	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3, H412	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1
Eye Dam. 1, H318	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2, H225	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1B, H314	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C, H314	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1, H317	SKIN SENSITISATION - Category 1
Skin Sens. 1A, H317	SKIN SENSITISATION - Category 1A
STOT RE 2, H373	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

Penguard FC Comp B

SECTION 16: Other information

STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3
-----------------	---

Date of printing : 25.02.2020

Date of issue/ Date of revision : 25.02.2020

Date of previous issue : 25.02.2020

Version : 4.01

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Penguard FC Comp B

Exposure Scenario: Use in coatings - Industrial use

Sector of Use	: Industrial use
Process Category	: PROC05 PROC07 PROC08a PROC10
Environmental release category(ies)	: ERC4

Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

Operational conditions and risk management measures

Control of worker exposure

Frequency and duration of use	: Covers daily exposures up to 8 hours
General - Operational conditions	: Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented
General - Risk management measures	: Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. See Section 8 for information on appropriate personal protective equipment.

Type of activity or process Risk management measures

Preparation of material for application	: Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Roller, spreader, flow application	: Provide extract ventilation to points where emissions occur.
Spraying - Manual	: Carry out in a vented booth provided with laminar airflow. or Provide a good standard of controlled ventilation (10 to 15 air changes per hour). and Wear a respirator conforming to EN140 with type A/P2 filter or better.

Control of environmental exposure

Organisational measures to prevent/limit release from site	: Prevent environmental discharge consistent with regulatory requirements.
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations. See Section 13 for additional waste treatment information.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional information

The exposure scenario for the mixture is based on the following substances:

REACH #: 01-2119488216-32

Penguard FC Comp B

Exposure Scenario: Use in coatings - Professional use

Sector of Use	: Professional use
Process Category	: PROC05 PROC08a PROC10 PROC11
Environmental release category(ies)	: ERC8a ERC8d

Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

Operational conditions and risk management measures

Control of worker exposure

Frequency and duration of use	: Covers daily exposures up to 8 hours
General - Operational conditions	: Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented
General - Risk management measures	: Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. See Section 8 for information on appropriate personal protective equipment.

Type of activity or process

Risk management measures

Preparation of material for application - Indoor	: Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour. or Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear a respirator conforming to EN140 with type A/P2 filter or better.
Preparation of material for application - Outdoor	: Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. or Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with type A/P2 filter or better.
Equipment cleaning and maintenance	: Drain down system prior to equipment break-in or maintenance. Avoid carrying out activities involving exposure for more than 4 hours.
Roller, spreader, flow application - Indoor	: Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear a respirator conforming to EN140 with type A/P2 filter or better.
Roller, spreader, flow application - Outdoor	: Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with type A/P2 filter or better.
Spraying - Manual - Indoor	: Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Wear a respirator conforming to EN140 with type A/P2 filter or better.
Spraying - Manual - Outdoor	: Ensure operation is undertaken outdoors. Wear a full-face respirator conforming to EN136 with Type A/P2 filter or better. Avoid carrying out activities involving exposure for more than 4 hours.

Control of environmental exposure

Organisational measures to prevent/limit release from site	: Prevent environmental discharge consistent with regulatory requirements.
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations. See Section 13 for additional waste treatment information.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional information

The exposure scenario for the mixture is based on the following substances:

REACH #: 01-2119488216-32