

Lady Design Pearl

Surface: Plaster/CMU/Concrete/Gypsum Board Partition

Primer Coat

One coat: Jotun Fenomastic Emulsion Primer:

Vol. solids: 25±2 %

Filler Coat

Two coats: Jotun Stucco:

Vol. solids: 50% ±2 %

Topcoats

Two coats: Jotun Fenomastic My Home Rich Matt

Vol. solids: 40±2 %

Properties

- VOC content 23.9 g/l (US EPA 24)
- Washability/Scrub Resistance >10,000 scrubs (DIN 53778)
- Hazardous Materials Free from:
 - Heavy Metals (ICP-AES)
 - APEO (BS 3762:90)
 - Formaldehyde (UV Spectroscopy)
 - Pthalates (GCMS)
- Burnish Resistance Gloss Change: 60° =0.1units 85° =0.9 units

Polish Resistance Gloss change: @ 60 = 0.4 units

- @ 85 = 6.9 units
- Contrast Ratio/whitenesss 97.00/94.82 (ASTM D2805-88)
- Practical Washability: Rating 0-2: (ASTM D4828:94)
- Colour rub off: Class A

(0 = AII stains removed & 2 = No stains removed)

(Class A = Best & Class E = Worst)



Top coats:

Two/Three coats Lady Design Pearl Vol. solids: 36±2 %, VOC: 61 g/l (ISO 11890 EU)