SPECIFICATION TOOL



Fenomastic My Home Rich Matt

Surface: Plaster/CMU/Concrete/Gypsum Board Partition

Primer Coat

One coat: Jotun Fenomastic Emulsion Primer:

Vol. solids: 25±2 %

Filler Coat

Two coats: Jotun Stucco:

Vol. solids: $50 \pm 2\%$

Topcoats

Two coats: Jotun Fenomastic My Home Rich Matt

Vol. solids are $40 \pm 2\%$

Properties

VOC content
23.9 g/l (US EPA 24)

Washability/Scrub Resistance
\(10.000 \) cerubs (DIN 52778)

>10,000 scrubs (DIN 53778)

• Hazardous Materials

Free from:

Heavy Metals (ICP-AES)
APEO (BS 3762:90)
Formaldehyde (UV Spectroscopy)
Pthalates (GCMS)

• Burnish Resistance

Gloss Change: 60° =0.1units 85° =0.9 units

Polish Resistance

Gloss change: @ 60 = 0.4 units @ 85 = 6.9 units

• Contrast Ratio/whitenesss 97.00/94.82 (ASTM D2805-88)

Practical Washability:

Rating 0-2: (ASTM D4828:94)

(0 = All stains removed & 2 = No stains removed)

• Colour rub off:

Class A

(Class A = Best & Class E = Worst)